

Part no	Section (mm)	Quantity	Working Drawing (Dimension in mm)	single/pc mm	total m	Weight kg / pc	total kg	Surface to be painted m ² / pc	to be total m ²	Total weight (finished) Galvanized kg	Remarks
T-1	Angle 100/100/12 ℓ = 1285	8		1285	10.28	22.22	177.76	0.51	4.08	180.25	
T-2	Plate 480/430/10	4		—	—	15.81	63.24	0.42	1.68	64.26	
T-3	a Channel ISMC 75-2225	4		2225	8.90	15.08	60.32	0.69	2.76	62.00	Part no T-3 (a,b) to be welded together as shown in detail
	b Rod ϕ 16mm ℓ = 3173	4	For the Bending of rod refer to detail 1:10	3173	12.69	5.01	20.04	0.16	0.64	20.43	
T-4	Plate 320/150/10	2		—	—	3.55	7.10	0.10	0.20	7.22	
T-5	Plate 280/70/8	16		—	—	1.14	18.24	0.04	0.64	18.63	

Part no	Section (mm)	Quantity	Working Drawing (Dimension in mm)	Length single/pc mm	total m	Weight kg/ pc	total kg	Surface to be painted m ² /pc	total m ²	Total weight (finished) Galvanized kg	Remarks
T-5	Plate 290 / 80 / 8	8	4 holes ϕ 21 mm thickness = 8 mm	—	—	1.37	10.96	0.05	0.40	11.20	
T-6	a Angle 65/65/6 ℓ = 1540	4	4 holes ϕ 16.5 mm thickness = 6 mm	1540	6.16	8.85	35.40	0.39	1.56	36.35	Part no T-6 (a,b) to be welded together as shown in welding detail.
	b Rod ϕ 16mm ℓ = 3172	2	ϕ 16	3172	6.34	5.00	10.00	0.16	0.32	10.20	
T-7	Plate 520 / 360 / 8	4	5 holes ϕ 16.5 mm 10 holes ϕ 21 mm thickness = 8 mm	—	—	10.34	41.36	0.34	1.36	42.19	
T-8	Plate 295 / 80 / 8	8	4 holes ϕ 21 mm thickness = 8 mm	—	—	1.40	11.20	0.05	0.40	11.44	
T-9	Plate 240 / 150 / 8	2	8 holes ϕ 16.5 mm thickness = 8 mm	—	—	2.15	4.30	0.07	0.14	4.38	